



**BE-8135TB - BE-8262TB**  
**ERGO™ Through Blade Slotted**  
**Screwdrivers with Impact Grip**  
**3.5-6.5 mm**



## PRODUCT DETAILS









- Impact screwdriver developed according to the scientific ERGO™ process
- For slotted head screws for fastening, loosening and chiselling
- Black oxide tip for higher accuracy
- Three-component handle for maximum user comfort, soft material with ridged surface provides superior grip and greater force transmission
- Maximum comfort with minimum effort thanks to an ergonomic design
- Easy to choose the right tip with the colour-coded handle
- Flat face to prevent rolling away
- Hexagon profile blade and bolster allow the use of a wrench for jobs that require more torque
- The blade continues through the handle with no loss of hammer blow energy. Metallic cap gives protection during jobs requiring high impact
- High-performance alloy steel blade with chrome plating, entirely hardened for high protection against corrosion, long life tool
- Standards: ISO 2380 and DIN 5264



**Follow the Fish!**



## PRODUCT ATTRIBUTES

| Product           |  |  |  |  |  |  |  |  |
|-------------------|---|---|---|---|--|---|---|---|
| <b>BE-8135TB</b>  | 0.6 mm  | 3.5 mm  | 75 mm   | 4 mm  | 27 mm  | 122 mm  | 197 mm  | 65 g  |
| <b>BE-8145TB</b>  | 0.8 mm  | 4.5 mm  | 100 mm  | 5 mm  | 27 mm  | 122 mm  | 222 mm  | 65 g  |
| <b>BE-8150TB</b>  | 1 mm  | 5.5 mm  | 100 mm  | 5 mm  | 27 mm  | 122 mm  | 222 mm  | 75 g  |
| <b>BE-8155TB</b>  | 1.2 mm  | 6.5 mm  | 125 mm  | 6 mm  | 36 mm  | 122 mm  | 247 mm  | 125 g   |
| <b>BE-8256TB</b>  | 1.6 mm  | 8 mm  | 150 mm  | 8 mm  | 36 mm  | 122 mm  | 272 mm  | 162 g   |
| <b>BE-8258TB</b>  | 1.6 mm  | 10 mm   | 175 mm  | 8 mm  | 36 mm  | 122 mm  | 297 mm  | 210 g   |
| <b>BE-8262TB</b>  | 2 mm  | 12 mm   | 200 mm  | 8 mm  | 36 mm  | 122 mm  | 322 mm  | 291 g   |
| <b>SBE-8135TB</b> | 0.6 mm  | 3.5 mm  | 75 mm   | 4 mm  | 27 mm  | 122 mm  | 197 mm  | 60 g  |
| <b>SBE-8145TB</b> | 0.8 mm  | 4.5 mm  | 100 mm  | 5 mm  | 27 mm  | 122 mm  | 222 mm  | 65 g  |
| <b>SBE-8150TB</b> | 1 mm  | 5.5 mm  | 100 mm  | 5 mm  | 27 mm  | 122 mm  | 222 mm  | 75 g  |
| <b>SBE-8155TB</b> | 1.2 mm  | 6.5 mm  | 125 mm  | 6 mm  | 36 mm  | 122 mm  | 247 mm  | 125 g   |

