

## 6700SM

1/4" Square Drive Sockets with Metric Hex Profile and High Polished Finish




## PRODUCT DETAILS

- Knurled shank for finger turning of free running fasteners
- Not suitable for machine operation or power tools
- Highly polished finish
- High-performance alloy steel

- $\bullet$  Less wear of the fastener thanks to Dynamic-Drive  $^{\text{TM}}$  profile
- Maximum load distribution and torque from the additional flank area
- Standards: ISO 2725/1174 and DIN 3124/3120
- SB: Retail pack on a plastic info card







## PRODUCT ATTRIBUTES

Product	0	L	D1	D2	Т	g
6700SM-4	4 mm	24.7 mm	6.8 mm	11,9 mm	6,5 mm	9 g
6700SM-4.5	4.5 mm	24.7 mm	7.4 mm	11,9 mm	7,5 mm	10 g
6700SM-5	5 mm	24.7 mm	8.1 mm	11,9 mm	7,5 mm	10 g
6700SM-5.5	5.5 mm	24.7 mm	8.7 mm	11,9 mm	8 mm	10 g
6700SM-6	6 mm	24.7 mm	9.3 mm	11,9 mm	8 mm	10 g
6700SM-7	7 mm	24.7 mm	10.8 mm	11,9 mm	8 mm	12 g
6700SM-8	8 mm	24.7 mm	11.9 mm	11,9 mm	8 mm	12 g
6700SM-9	9 mm	24.7 mm	13.4 mm	12,4 mm	8 mm	12 g
6700SM-10	10 mm	24.7 mm	14.5 mm		9 mm	15 g
6700SM-11	11 mm	24.7 mm	15.9 mm	14,1 mm	11,5 mm	18 g
6700SM-12	12 mm	24.7 mm	16.9 mm	15 mm	11,5 mm	18 g
6700SM-13	13 mm	24.7 mm	18 mm	15,6 mm	11,5 mm	20 g
6700SM-14	14 mm	24.7 mm	19.6 mm	16 mm	11,5 mm	22 g
SB6700SM-4	4 mm	24.7 mm	6.8 mm	11,9 mm	6,5 mm	9 g
SB6700SM-4.5	4.5 mm	24.7 mm	7.4 mm	11,9 mm	7,5 mm	10 g
SB6700SM-5	5 mm	24.7 mm	8.1 mm	11,9 mm	7,5 mm	10 g
SB6700SM-5.5	5.5 mm	24.7 mm	8.7 mm	11,9 mm	8 mm	10 g
SB6700SM-6	6 mm	24.7 mm	9.3 mm	11,9 mm	8 mm	10 g
SB6700SM-7	7 mm	24.7 mm	10.8 mm	11,9 mm	8 mm	12 g
SB6700SM-8	8 mm	24.7 mm	11.9 mm	11,9 mm	8 mm	20 g
SB6700SM-9	9 mm	24.7 mm	13.4 mm	12,4 mm	8 mm	12 g
SB6700SM-10	10 mm	25 mm	14.5 mm		9 mm	20 g
SB6700SM-11	11 mm	24.7 mm	15.9 mm	14,1 mm	11,5 mm	30 g
SB6700SM-12	12 mm	24.7 mm	16.9 mm	15 mm	11,5 mm	30 g
SB6700SM-13	13 mm	24.7 mm	18 mm	15,6 mm	11,5 mm	30 g
SB6700SM-14	14 mm	24.7 mm	19.6 mm	16 mm	11,5 mm	30 g

