



BAHCO Sandflex® Top Fabricator 3853

3853 Sandflex® Top Fabricator
Sandflex® Top Fabricator
Bandsaw Blades

PRODUCT DETAILS







- For cutting of structural steel, tubes and profiles
- HSS tooth material for long tool life
- Special PF tooth shape, reduces out of square cutting, stripped teeth, vibration, pinching consequently less broken blades
- New, improved high speed steel tooth edge gives a combination of higher hardness and higher toughness for long tool life
- Particularly well suited for mitre (angle) cutting
- 5/8 TPI available for thin walled and single work pieces, as well as bundles
- Maximum cutting performance from the specially designed tooth design
- Long tool life thanks to the special HSS teeth
- Well suited for mitre (angle) cutting
- Double set makes the teeth stronger, more resistant to tooth stripping and longer lasting
- Available with wide set for heavy structural, eliminating pinching



Follow the Fish!



PRODUCT ATTRIBUTES

Product						
3853-20-0.9-5/7-VS	20 mm	3/4 in	0.9 mm	0.035 in	5/7	PF
3853-20-0.9-8/11-VS	20 mm	3/4 in	0.9 mm	0.035 in	8/11	PF
3853-27-0.9-3/4	27 mm	1 in	0.9 mm	0.035 in	3/4	PF
3853-27-0.9-4/6	27 mm	1 in	0.9 mm	0.035 in	4/6	PF
3853-27-0.9-5/8	27 mm	1 in	0.9 mm	0.035 in	5/8	PF
3853-27-0.9-5/7-VS	27 mm	1 in	0.9 mm	0.035 in	5/7	PF
3853-27-0.9-8/11-VS	27 mm	1 in	0.9 mm	0.035 in	8/11	PF
3853-34-1.1-2/3	34 mm	1-1/4 in	1.1 mm	0.042 in	2/3	PF
3853-34-1.1-3/4	34 mm	1-1/4 in	1.1 mm	0.042 in	3/4	PF
3853-34-1.1-4/6	34 mm	1-1/4 in	1.1 mm	0.042 in	4/6	PF
3853-34-1.1-5/8	34 mm	1-1/4 in	1.1 mm	0.042 in	5/8	PF
3853-34-1.1-5/7-VS	34 mm	1 1/4 in	1.1 mm	0.042 in	5/7	PF
3853-34-1.1-8/11-VS	34 mm	1 1/4 in	1.1 mm	0.042 in	8/11	PF
3853-41-1.3-2/3	41 mm	1-1/2 in	1.3 mm	0.05 in	2/3	PF
3853-41-1.3-2/3-W	41 mm	1-1/2 in	1.3 mm	0.05 in	2/3-W	PF-W
3853-41-1.3-3/4	41 mm	1-1/2 in	1.3 mm	0.05 in	3/4	PF
3853-41-1.3-3/4-W	41 mm	1-1/2 in	1.3 mm	0.05 in	3/4-W	PF-W
3853-41-1.3-4/6	41 mm	1-1/2 in	1.3 mm	0.05 in	4/6	PF
3853-41-1.3-5/8	41 mm	1-1/2 in	1.3 mm	0.05 in	5/8	PF
3853-41-1.3-5/7-VS	41 mm	1-1/2 in	1.3 mm	0.05 in	5/7	PF
3853-54-1.3-3/4	54 mm	2 in	1.3 mm	0.05 in	3/4	PF
3853-54-1.3-3/4-W	54 mm	2 in	1.3 mm	0.05 in	3/4	PF
3853-54-1.3-5/8	54 mm	2 in	1.3 mm	0.05 in	5/8	PF
3853-54-1.6-2/3	54 mm	2 in	1.6 mm	0.062 in	2/3	PF
3853-54-1.6-2/3-W	54 mm	2 in	1.6 mm	0.062 in	2/3-W	PF-W
3853-54-1.6-3/4	54 mm	2 in	1.6 mm	0.062 in	3/4	PF
3853-54-1.6-3/4-W	54 mm	2 in	1.6 mm	0.062 in	3/4-W	PF-W
3853-54-1.6-4/6	54 mm	2 in	1.6 mm	0.062 in	4/6	PF
3853-67-1.6-2/3	67 mm	2-5/8 in	1.6 mm	0.062 in	2/3	PF
3853-67-1.6-2/3-W	67 mm	2-5/8 in	1.6 mm	0.062 in	2/3-W	PF-W
3853-67-1.6-3/4	67 mm	2-5/8 in	1.6 mm	0.062 in	3/4	PF
3853-67-1.6-3/4-W	67 mm	2-5/8 in	1.6 mm	0.062 in	3/4-W	PF-W
3853-67-1.6-5/8-W	67 mm	2-5/8 in	1.6 mm	0.062 in	5/8-W	PF-W

Follow the Fish!

