

BETON TROWEL

CONCRETE FINISHING
& COMPACTION



CONCRETE VIBRATOR HUMDINGER

Humdinger electric hand held flex drive concrete vibrators.

- Powerful lightweight power unit with robust motor protection
- Flexible shafts from 1m to 6m
- Head diameters from 25mm to 58mm
- Double insulated 2,3 kW motors, 115V & 230V



SPECIFICATIONS:

Model		Voltage	kW	Hz	Motor Speed	Weight
HVU110	Humdinger Electric Power Unit	115V	2,3	50/60	18.000	5,5
HVU220	Humdinger Electric Power Unit	230V	2,3	50/60	18.000	5,5

Model	Vib diam	Length	Weight	Frequency	Amplitude
HDV25/2	25mm	2m	5,50Kg	13.700	1,12
HDV25/6	25mm	6m	8,50Kg	13.700	1,12
HDV28/6	28mm	6m	9,40Kg	16.800	1,20
HDV38/1	38mm	1m	4,96Kg	16.200	1,54
HDV38/2	38mm	2m	6,26Kg	16.200	1,54
HDV38/3	38mm	3m	7,56Kg	16.200	1,54
HDV38/4	38mm	4m	8,86Kg	16.200	1,54
HDV38/5	38mm	5m	10,36Kg	16.200	1,54
HDV38/6	38mm	6m	11,86Kg	16.200	1,54
HDV48/3	38mm	3m	8,90Kg	15.600	1,54
HDV48/4	48mm	4m	10,20Kg	15.600	1,65
HDV48/5	48mm	5m	11,70Kg	15.600	1,65
HDV58/5	58mm	5m	12,50Kg	15.000	1,68

