




High Performance

SLTT INOX, our Turbo Flap Disc to work on stainless steel

Ordering example: A27201150400045



**Packing unit:**  
10 pcs. per type  
 $v_{max}$ : 80 m/s  
Z POWER – Abrasive cloth using Zirconia Alum. Oxide with special coating containing active grinding additives



Description	Grits	D mm	H mm	n max (U/min)	Product-Number	recommended for
SLTT 115	Z Power 40	115	22,23	13.300	A27201150400045	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 115	Z Power 60	115	22,23	13.300	A27201150600045	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 125	Z Power 40	125	22,23	12.200	A27201250400045	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 125	Z Power 60	125	22,23	12.200	A27201250600045	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 150	Z Power 40	150	22,23	10.200	A27201500400045	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 178	Z Power 40	178	22,23	8.500	A27201780400045	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 178	Z Power 60	178	22,23	8.500	A27201780600045	① ② ③ ④ ⑤ ⑥ ⑦ ⑧

Eigenschaften:


- No glazing or heating of flaps, owing to top size coating
- equally efficient for both edge and surface applications
- iron-sulphur-chlorine free



High Performance

SLTT Heavy Duty, our Turbo Flap Disc for roughest application

Ordering example: A27201150400050



**Packing unit:**  
10 pcs. per type  
 $v_{max}$ : 80 m/s  
Ceramic – Abrasive cloth ceramic grain



Description	Grits	D mm	H mm	n max (U/min)	Product-Number	recommended for
SLTT 115	Ceramic 40	115	22,23	13.300	A27201150400050	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 115	Ceramic 60	115	22,23	13.300	A27201150600050	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 125	Ceramic 40	125	22,23	12.200	A27201250400050	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 125	Ceramic 60	125	22,23	12.200	A27201250600050	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 150	Ceramic 40	150	22,23	10.200	A27201500400050	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 178	Ceramic 40	178	22,23	8.500	A27201780400050	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 178	Ceramic 60	178	22,23	8.500	A27201780600050	① ② ③ ④ ⑤ ⑥ ⑦ ⑧

Properties:


- particularly robust for edge grinding, on heat treated steels, surface scale or coated surfaces
- iron-sulphur-chlorine free



High Performance

SLTT Steel, our Turbo Flap Disc for universal application on steel and aluminium

Ordering example: A27201150400065



**Packing unit:**  
10 pcs. per type  
 $v_{max}$ : 80 m/s  
ZK – Abrasive cloth with Zirconia Alum. Oxide



Description	Grits	D mm	H mm	n max (U/min)	Product-Number	recommended for
SLTT 115	ZK 40	115	22,23	13.300	A27201150400065	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 115	ZK 60	115	22,23	13.300	A27201150600065	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 125	ZK 40	125	22,23	12.200	A27201250400065	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 125	ZK 60	125	22,23	12.200	A27201250600065	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 150	ZK 40	150	22,23	10.200	A27201500400065	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 150	ZK 60	150	22,23	10.200	A27201500600065	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 178	ZK 40	178	22,23	8.500	A27201780400065	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
SLTT 178	ZK 60	178	22,23	8.500	A27201780600065	① ② ③ ④ ⑤ ⑥ ⑦ ⑧

Properties:

- tough grain with a high degree of resistance to pressure
- quicker, more aggressive and longer tool life when compared with our current ZKS quality

