

MARELD
PRO LIGHTING®



WORK LIGHT CANOPUS
3000 RE

- Impact resistant
- Colour temperature between 2700-6500 K
- Dimmer function
- RA 95
- IP 65



WORK LIGHT CANOPUS 3000 RE

Rechargeable. High colour reproduction (RA95). Colour temperature can be set steplessly between 2700-6500 K. There is also a dimmer function that allows you to control brightness. Can also be used with a mains connection, but will then automatically illuminate at 50 % output. Extremely impact resistant and robust design. Impact resistance IK08.



ART. NO.	690000484
Mareld Segment	Performance
Depth	80 mm
ETIM class code	EC000346
Light source	LED
LED technology	COB
Colour temperature	2700-6500, 6500 K, RA 95
Light flux	3000 lm
Effect	30 W
Voltage	12 V
Rechargeable	Yes
Charging time	3 h
Operating time 50% output	3 h
Operating time 100% output	1.5 h
Operating time energy saving output	15 h
Lamp life	30000 h
Working temperature	-20 – +50 °C
Cable type	H05RN-F-2G 1,0 mm
Cable length	5 m
Width	230 mm
Height	225 mm
Colour designation popular name	Petrol/black
Enclosure class IP	IP65
CE marking	Yes

MARELD

PRO LIGHTING®

WWW.MARELDPROLIGHTING.COM

MARELD PRO LIGHTING

Phone: +46 322 60 60 00

info@mareldprolighting.com

mareldprolighting.com