



3M™ Speedglas™ Welding Helmets, G5-03 Pro and G5-03 Pro Air

Product Description

- Attachment system for additional protective accessories
- TAP function suitable for grinding and cutting
- Task light as an accessory, powered by 3M™ Adflo™ Battery (where applicable) or a separate head band mounted battery
- Adjustable air flow distribution (Pro Air)
- Class TH3 CE, NPF 500 (Pro Air with particle filters)
- Class TH2 CE, NPF 50 (Pro Air) with gas and vapour filters and breathing tube
- Compatible with selected 3M safety helmets (Pro)



Applications

This product helps protect the wearer's eyes and face from sparks, spatter, harmful ultraviolet radiation (UV) and infrared radiation (IR) resulting from certain arc gas welding processes. The G5-03 Pro Air welding helmet also protects against certain airborne contaminants when used with an approved air delivery unit.

3M™ Speedglas™ welding helmet G5-03 is designed for:


- Most welding processes, such as: MMA (Stick), MIG/MAG, TIG, Low amp TIG
- Cutting
- Grinding

Approvals

The PPE is marked and is in conformity with the applicable National and European Regulations, Directives and Standards as listed in the table below, which also contains information about the Authorized Body that has issues the type-Examination certificate for the PPE (Module B) and when applicable, the Authorized Body responsible for the surveillance of the quality system of the manufacturing of the PPE (Module D). The applicable type-examination Certificates and Declaration of Conformity are available at www.3m.com/welding/certs.

3M™ Speedglas™ Welding Helmets, G5-03 Pro and G5-03 Pro Air

Table 1: Approvals

Standard/Directive/Regulation	Name
*ISO 16321-1	Eye and face protection for occupational use Part 1: General requirements
*ISO 16321-2	Eye and face protection for occupational use Part 2: Additional requirements for protectors used during welding and related techniques
*EN 12941:1998 A1:2003 +	Respiratory protective devices - Powered filtering devices incorporating a helmet or hood (Pro Air)
*EN 14594:2018	Respiratory protective devices - Continuous flow compressed air line breathing apparatus - Requirements, testing, marking (Pro Air)
*See product markings for approval information	
(EU) 2016-425	Personal Protective Equipment (PPE) Regulation
	Personal Protective Equipment Regulations (Regulation 2016/425 on personal protective equipment, as amended to apply in GB)
Notified Body No. 0196 Module B	DIN CERTCO Gesellschaft fuer Konformitaetsbewertung mbH, Alboinstrasse 56, 12103 Berlin, Germany
Approved Body No. 2571 (Module B)	TUV Rheinland UK, Friars Gate (Third Floor), 1011 Stratford Road, Shirley, Solihull B90 4BN, UK
Notified Body No. 2797 Module B, Module D	BSI Group, The Netherlands B. V. Say Building, John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
Approved Body No.0086 Module B, Module D	BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, UK
 Manufacturer	3M Svenska AB, Ernst Hedlunds väg 35, 785 30 Gagnef, Sweden
EU Contact Address	3M Svenska AB, Ernst Hedlunds väg 35, 785 30 Gagnef, Sweden
UK Contact Address	3M UK, Cain Rd, RG12 8HT, UK

 = Auto darkening welding filters shall be disposed of as electrical and electronic waste.

Limitations of Use

- Only use with original 3M spare parts and accessories listed in the reference leaflet and within the usage conditions given in the Technical Specification.
- The use of substitute components, decals, paint or other modifications not specified in these user instructions might seriously impair protection and may invalidate claims under the warranty or cause the product to be noncompliant with protection classifications and approvals.
- Eye protectors worn over standard ophthalmic spectacles may transmit impacts thus creating a hazard to the wearer.
- The Speedglas welding helmet is not designed for overhead welding/cutting operations when there is a risk of burns from falling molten metal.
- Materials which may come into contact with the wearer's skin are not known to cause allergic reactions to the majority of individuals. These products do not contain components made from natural rubber latex.

Welding Helmet G5-03 Pro Air

- Do not use for respiratory protection against unknown atmospheric contaminants or when concentrations of contaminants are unknown or immediately dangerous to life or health (IDLH).
- Do not use in atmospheres containing less than 19.5% oxygen (3M definition. Individual countries may apply their own limits on oxygen deficiency. Seek advice if in doubt).
- Do not use these products in oxygen or oxygen-enriched atmospheres.
- Leave the contaminated area immediately if: Any part of the system becomes damaged, airflow into the head top decreases or stops, breathing becomes difficult, dizziness or other distress occurs, you smell, or taste contaminants or irritation occurs.
- High winds above 2 m/s, or very high work rates (where the pressure within the head top can become negative) can reduce protection. Adjust equipment as appropriate or consider an alternative form of respiratory protective device.
- Do not use with beards or other forms of facial hair that may inhibit contact between the face and the product thus preventing a good seal.
- Do not remove the welding helmet or turn off the air supply until you have vacated the contaminated area.
- Respiratory filters shall only be fitted to the turbo unit and not directly to the helmet/hood.

Welding Helmet G5-03 Pro

- This product is not a respirator. Welding may produce high levels of welding fume or other airborne contaminants which may exceed the Workplace Exposure Limit (WEL). As a result, users and their employer must determine the expected hazards, and if needed select appropriate respiratory protection. Properly selected, used, and maintained respirators in a full respiratory protection program help protect against certain airborne contaminants by reducing airborne concentrations in the wearer's breathing zone below the WEL. Failure to use respirators or misuse of respirators may result in overexposure to contaminants and lead to sickness or death.

Materials

Helmet:	PPA
Side windows:	PC
Front frame:	PPA
Head band:	PA, PP, TPE, PE
Face seal:	Co/Polyester 50/50% + PP

Technical Specifications

Specification:	Value:
Weight welding helmet (excl. headband and welding filter)	G5-03 Pro: 280g G5-03 Pro Air: 530 g
Weight headband	145 g
Head sizes	50-64
Operating Conditions	-5 °C to +55 °C, RH ≤ 90%, non condensing conditions
Storage Conditions	-20 °C to +55 °C, RH ≤ 90%, non-condensing conditions
Short-term storage temperature conditions, non-operating <1 month	
Welding helmet	-30 °C to +60 °C, RH ≤ 90%, non-condensing conditions
Expected service life	5 years depending on condition of use

Spare Parts, Accessories, and Consumables

Part number	Description
16 90 40	Neck protection rigid
16 90 41	Neck protection in fabric (small)
16 90 42	Neck protection in fabric (large)
16 90 43	Neck protection in leather
16 90 20	Head protection in fabric
16 90 21	Head protection florescent yellow
16 90 22	Head protection in leather
16 90 23	Head protection in fabric (large)
16 90 24	Scrape guard G5-01/03
16 90 30	Shroud
16 90 35	Extended cover kit (shroud and large head cover in fabric)
16 91 00	Protective hood black/grey
16 92 00	Task Light, including mounting parts and cables
16 92 15	Task Light Kit, (light, cable, holder with cable and battery)
16 92 10	Long power cable for task light
16 92 11	Short power cable for task light
16 92 05	Protection plate for task light, pkg. of 5
16 92 16	Welding helmet task light holder for battery with attachment parts
16 92 17	Task Light
19 17 70	Safety helmet adapters type A (X5000)
19 71 71	Safety helmet adapters type B (G3000/H700)
19 80 16	Sweatband towelling, pkg. of 3
19 80 17	Sweatband fleecy cotton, pkg. of 3
19 80 18	Sweatband leather
53 62 10	Cushion part
53 62 11	Large head rest
61 05 01	Front frame
61 32 00	Headband with assembly parts
61 37 00	Air duct breathing tube (short) incl. holder
61 37 01	Holder for breathing tube
61 40 00	Face seal
61 60 00	Pivot and sliding mechanism, including pivot knobs
61 60 02	Pivot knobs
61 60 03	Headband back part
63 18 95	Welding Helmet G5-03 Pro, without welding filter, front frame and headband
63 20 15	Side windows cover plates
63 28 90	Welding Helmet G5-03 Pro Air with air duct and airflow controls, without welding filter, front frame
79 01 05	Carry bag
ACK081	Rechargeable battery
AL2AI/SP	Battery Charging Cable for ACK081
G3001NVE	3M™ Safety Helmet G3001
H-701T-SF	3M™ Safety Helmet H-701R (non-vented)
X5500NVE	3M™ Safety Helmet X5500NVE (non-vented)

Important Notice

The use of the 3M product described within this document assumes that the user has previous experience of this type of product and that it will be used by a competent professional. Before any use of this product, it is recommended to complete some trials to validate the performance of the product within its expected application. All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user. Compliance to the information and specification relative to the 3M product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M group (which cannot verify or control those elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control. Warranty conditions for 3M products are determined with the sales contract documents and with the mandatory and applicable clause, excluding any other warranty or compensation.



Personal Safety Division
3M United Kingdom plc
3M Centre
Cain Road, Bracknell
Berkshire RG12 8HT
Tel: 0870 60 800 60
www.3M.co.uk/safety

3M Ireland Limited
The Iveagh Building
The Park, Carrickmines
Dublin 18
T: 1 800 320 500

3M PSD products are occupational use only.

© 3M 2023. All rights reserved.
3M is a trademark of 3M Company and its affiliates.
All other trademarks are property of their respective owners. Please recycle. www.speedglas.com
V1 2023